



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (Cd/m ²)	*RATED LIFE (HRS)
CF20325-24B	8400 Kelvin x = .290 REF. y = .305 REF.	**1830 MAX.	735 @ 5mA	5.0 TYP. 7.0 MAX.	46,000 TYP.	20,000 MIN. 40,000 AVG.

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

**MAY BE HIGHER WHEN MOUNTED IN METAL RAIL AND USING INPUT HARNESS, REF. 2250 Vrms Max. @ 0 C.

		 THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION					
						TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP					
A		CHANGE BRIGHTNESS TO 46,000 TYP.	5/3/05	DRAWN BY L. WENGSTROM	APPVD BY J.K.	DATE 5/3/05	SIZE A	FSCM NO. 55335	DRAWING NO. CF20325-24B		
		RELEASED	4/15/04	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 4/15/04	REVISION DATE 5/3/05	REV. NO. A	SHEET 1 OF 1
REV. NO.	DESCRIPTION/ECO NUMBER		APPVD DATE								